

->HYM001-现代起亚-私板-09-17 IX35 带功放 11-
14 索纳塔 8 带功放

威驰协议盒 [Hiworld 威驰协议盒](#) 2019-10-25 17:17

适用车型：09-17 IX35 带功放 11-14 索纳塔 8 带功放

1. can 盒子端



PIN	定义	PIN	定义
1	BATT（12V 输入）	2	GND
3	RCA_L	4	RCA_R
5	ACC_IN（点火信号检测）	6	SWC_GND（SWC 地）
7	RCA_GND	8	SWC（方向盘按键输入）
9	CAN_H（CAN 输入）	10	CAN_L（CAN 输入）
11		12	
13	UART_RX（解码器串口输入）	14	UART_TX（解码器串口输出）
15	RESET（解码器 MCU 复位输入）	16	ACC_OUT（点火信号输出）
17	SPDIF_TXN	18	SPDIF_TXP
19	SPDIF_GND	20	

2. Ix35 汽车尾线端



Part A

Part B

Part A 管脚位置说明

1	2	3	4	5	6	7	8	9
10	11	12	13	14	15	16	17	18

A1~A4: 喇叭线 **A5:** SPDIF_GND **A6:** SPDIF_TXN **A8:** ILL
A10~A13: 喇叭线 **A15:** SPDIF_TXP **A17:** GND **A18:** ANT

Part B 管脚位置说明

1	2	3	4	5	6	7	8	9	10	11	12
13	14	15	16	17	18	19	20	21	22	23	24

B1: CAN H **B4:** SWC+ **B6:** USB+ **B7:** USB VDD **B8:** AUX_R
B9: AUX_GND **B11:** ACC **B12:** BAT+ **B13:** CANL **B17:** SWC-
B18: USB- **B19:** USB GND **B21:** AUX_L **B24:** GND

3. 接线方法

原车端	盒子端	主机端
A5	----- Pin 19	
A6	----- Pin 17	
A15	----- Pin 18	
B1	----- Pin 9	
B13	----- Pin 10	
B4	----- Pin 8	
B17	----- Pin 6	
B11	----- Pin 5	
B12	----- Pin 1	
B24	----- Pin 2	
	Pin 13、14	----- 主机串口

4. 产品质保说明

客户收到我司产品之日起 18 个月内，因车厂车型换代出现的原车总线协议变更或我司原因导致的软件升级，我司提供免费的产品升级维护。

Disclaimer

Information furnished is believed to be accurate and reliable. However, Hiworld assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Hiworld. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied.

The Hiworld logo is a registered trademark of Hiworld
All other names are the property of their respective owners.

2011 Hiworld - All Rights Reserved

Hiworld